

Stainless Steel Compression Spring

Standard: GB/T1239.6-1992

Material: SUS301,304,18/8,0Cr18Ni9,X5CrNi1810,X10Cr13,410S21, if you need to use other stainless steel, please let us know.

Heat Treatment: None for normal, If you have special requirement, please let us know.

Finish: None.

Direction: Normal is right hand/dextrorotation, if you want left hand, please let us know.

Tensile strength: 700N/mm²

Stainless Steel Compression Spring is designed to operate with a compression load, so the spring gets shorter as the load is applied to it.

"Stainless Steel" - With the addition of 12% chromium to iron, stainless steel is formed. The chromium protects the iron against most corrosion or red colored rust; thus the term "stainless steel". The ability of stainless to form a thin layer of protection on its outside surface, called a "passive film", is its most important characteristic in preventing corrosion.

"18-8" - 300 series stainless steel having approximately (not exactly) 18% chromium and 8% nickel. The term "18-8" is used interchangeably to characterize fasteners made of 302,302HQ,303,304,384, XM7, and other variables of these grades with close chemical compositions. There is little overall difference in corrosion resistance among the 18-8 types, but slight differences in chemical composition do make certain grades more resistant than others against particular chemicals or atmospheres.

Austenitic - Refers to 300 series stainless, the most popular of the stainless alloys accounting for 85%-90% of stainless fasteners sold Named for sir Robert Williams Austen, an English metallurgist, austenitic stainless is a crystal structure formed by heating steel, chromium, and nickel to a high temperature where it forms the characteristics of 300 series stainless steel.

The typical **Stainless Steel Compression Spring** as below



And below is the common drawing for this kind:

